

Detail No.: **51.55**  
 Date: **March 2022**  
 Page: **1 of 2**

**Notes:**

1. StoPanel® Precast ci is a lightweight, energy efficient pre-fabricated exterior wall panel with a continuous air & moisture barrier, XPS exterior insulation and a variety of integral decorative & protective finish options to replicate precast concrete; all at a fraction of the weight of precast concrete.
2. XPS insulation: ASTM C 578, Type IV compliant.
3. Z-Clip Furring and metal Perimeter Channel set in wet Sto RapidGuard. Cover fastener heads with dab of Sto RapidGuard.
4. Minimum 3.4 lb./yd<sup>2</sup> self-furred galvanized steel diamond mesh metal lath in compliance with ASTM C 847.
5. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

**ATTENTION**


Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, [www.stocorp.com](http://www.stocorp.com).

Property of Sto Corp. All Rights Reserved.

[www.stopanel.com](http://www.stopanel.com)





Detail No.: 51.55  
 Date: March 2022  
 Page: 2 of 2

**Notes:**

1. StoPanel® Precast ci is a lightweight, energy efficient pre-fabricated exterior wall panel with a continuous air & moisture barrier, XPS exterior insulation and a variety of integral decorative & protective finish options to replicate precast concrete; all at a fraction of the weight of precast concrete.
2. XPS insulation: ASTM C 578, Type IV compliant.
3. Z-Clip Furring and metal Perimeter Channel set in wet Sto RapidGuard. Cover fastener heads with dab of Sto RapidGuard.
4. Minimum 3.4 lb./yd<sup>2</sup> self-furred galvanized steel diamond mesh metal lath in compliance with ASTM C 847.
5. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

U.S. Patent No.8,919,062 B1

**ATTENTION**

Property of Sto Corp. All Rights Reserved.

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, [www.stocorp.com](http://www.stocorp.com).

[www.stopanel.com](http://www.stopanel.com)

